



INSPECTION SERVICES AND ENGINEERING CERTIFICATION

PHONE: 780.870.1547 EMAIL: operations@indexndt.ca Head Office Mail: P.O. Box 10524, Lloydminster, AB T9V 3A6

INSPECTION REPORT

EQUIPMENT LOCATION:	Lloydminster, Alberta				NDT PROCEDURE#:	INSP-001			
EXAMINATION COVERAGE:	RANDOM:	5%	10%	25%	50%	75%	100%	X	
ACCEPTANCE CRITERIA:	CSA W59	ISO 9927-1		CAOEC RP		OTHER:		X	
INSPECTION METHOD:	VT	X	UT	X	MT WET FLOURESCENT	X	MT WET BLACK		MT DRY RED
EQUIPMENT INFO:	BLACK LIGHT MAKE - INOVA				LIGHT METER # 1822158		MAG COIL # RC1-30120121		

CLIENT:	K&S Power Tongs	UNIT/RIG:	KSV001
EQUIPMENT:	Volant Tool	MAKE/MODEL:	Volant CRTi3-7.0
REPORT#:	IDX-3151	SERIAL NUMBER:	KSV001

EQUIPMENT PHOTOS



INSPECTION RESULTS

ACCEPTABLE:	X	REJECTED:	DATE OF INSPECTION:	March 29, 2023
TECHNICIAN:				
<div></div>			Part: Serial#:	
			Mandrel - 82306-03-445A01-08	
			Cage - 82856-4459A02-12	
			Upper Cam - 81190-4445A04-07	
			Lower Cam - 81191-4459A05-08	
			Cam Latch - 80813-4459A05-05	
			Cam Int - 80810-4459A03-04	
			Die - 80987-02-439E A20-09	
			Die - 80987-02-439E A20-11	
			Die - 80987-02-439E A20-12	
Die - 80987-02-402E B07-09				
Die - 80987-02-402E B07-08				
			Material Thickness: 1.299"/ 1.295"/ 1.297"/ 1.295"/ 1.297"	
			REPAIRS: NA	

QUALITY ASSURED INSPECTIONS FOR QUALITY ASSURED BUSINESSES

*Except as provided herein, Index NDT Inspections Ltd. makes no warranty, express or implied with respect to the mechanical or other conditions of the equipment inspected by us. Index NDT Inspections Ltd. shall only be responsible in the event of damage resulting directly from their inspection, and in no event, shall the liability of Index NDT Inspections Ltd. exceed the cost of inspection. Our organization assumes only the responsibility of locating defects in the inspected components and welds made accessible at the time of inspection. All equipment should be cleaned to allow access to all welds and critical components. It is of the utmost importance that the unit's owner be aware that excessive coating over 10 mils can severely mask the detection of discontinuities while utilizing standard inspection techniques. We are not responsible for the mechanical or other conditions assembled condition except at customer's request.

HN-INCLUSION P-POROSITY IUC-INTERNAL UNDERCUT EUC-EXTERNAL UNDERCUT S-SLACK C-CRACK IP-INCOMPLETE PENETRATION N-F-NON-FUSION CR-CRACK P-PIN HOLE D-DISCONTINUITY



Certificate of Testing

Volant Oil Tools Inc.
4110 56 Avenue NW
Edmonton AB T6B 3R8
Canada

t +1 780.490.5185
f +1 780.437.2187
info@volantproducts.ca
www.volantproducts.ca

Unit Name:

Part Number:

ID Number: *KSV001*

Unit Description:

Load Testing

Test Parameters

Target Test Load: 960 kips Minimum Hold Time: 300 s

Test Summary

Test Components									Test Equipment	
Part Number	Part Name	Serial Number	Passed	Procedure	Actual Test Load	Hold Time	Test ID	Test Date	Identifier	Calibration Due
82306-03	Mandrel, CRTi2-7.0, 320T, 4.5IF, SR2	4459A01-08	Passed	102870	961 kips	352 s	L01-001431	Dec 2, 2019	VLF-01	Mar 11, 2020

DELAYED USE

Date of 1st Use: *January 6, 2020*
Job #: *23001*
Signed By: *[Signature]*

This is to certify that the equipment listed was tested in accordance with the referenced Procedure(s) to meet the Proof testing requirements of API-8C, 5th Edition

Signed:

Steven Hargreaves,
Manager, Quality Assurance,
Volant Oil Tools Inc.

Date: Dec 4, 2019



ISO 9001
Quality